



FRESATO PHILLIPS

 Articolo		LUNG. mm	mm	Descrizione	
12125	PH 1	33	6	INSERTO FILETTATO ATT.M5 PH1 L.33	1
PH2M5D6L31	PH 2	31	6	INSERTO FILETTATO ATT.M5 PH2 L.31	1
PH2M5D7L31	PH 2	31	7	INSERTO FILETTATO ATT.M5 PH2 L.31 D7	1
12126	PH 2	33	7	INSERTO FILETTATO ATT.M5 PH2 L.33	1
12126W	PH 2	33	7	INSERTO FILETTATO ATT.M5 PH2 L.33 ALTA RES.	1
12127	PH 2	33	6	INSERTO FILETTATO ATT.M5 PH2 L.33 D6	1
12127W	PH 2	33	6	INS. FILETTATO ATT.M5 PH2 L.33 D6 ALTA RES.	1
12141	PH 1	45	6	INSERTO FILETTATO ATT.M5 PH1 L.45	1
12141R	PH 1	45	4,5	INSERTO FILETTATO ATT.M5 PH1 L.45 D4,5	1
12142	PH 2	45	6	INSERTO FILETTATO ATT.M5 PH2 L.45	1
12142W	PH 2	45	6	INSERTO FILETTATO ATT.M5 PH2 L.45 ALTA RES.	1
12142R	PH 2	45	7 + 5	INSERTO FILETTATO ATT.M5 PH2 L.45 D7+D5	1

Caratteristiche

FRESATO PHILLIPS®
attacco: M 5
impronta: DIN 5260, PH